



MOWER SPECIFICATIONS

COMPACT OUTLAW MODELS



| | | |
|-----------------------------------|---|---|
| Cutting Width | 4200/42" | 4200/42" |
| Cutting Height | 1.5"–4.5" with Deck Height Control System | 1.5"–4.5" with Deck Height Control System |
| Blades | 4200/7/32" x 2 1/2" x 14 1/2", High Lift, Heat Treated 4800/1/4" x 2 1/2" x 16 1/2", High Lift, Heat Treated | 4200/7/32" x 2 1/2" x 14 1/2", High Lift, Heat Treated 4800/1/4" x 2 1/2" x 16 1/2", High Lift, Heat Treated |
| Lift and Height Adjustment | Foot-Assist Manual Deck Lift | Foot-Assist Manual Deck Lift |
| Blade Belt | Single V-Belt Spring Tension | Single V-Belt Spring Tension |
| Anti-Scalp Rollers | 4200/4 Total 4800/4 Total (2 on front, 2 in rear) | 4200/4 Total 4800/4 Total (2 on front, 2 in rear) |
| Deck Flotation | Floats on (4) 1/4" Deck Hangers | Floats on (4) 1/4" Deck Hangers |
| Deck Thickness | 3/16" Thick Solid Steel | 3/16" Thick Solid Steel |
| ENGINE | | |
| Gross Horsepower | 726 Air-Cooled Kawasaki FX 691 | 810cc Vanguard |
| Cylinders | V-Twin | 90 Degree V-Twin |
| Displacement | 726 cc | 810 cc |
| Maximum Torque | 40 ft. lbs. @ 2600 RPM | 42 ft. lbs. @ 2400 RPM |
| Fuel Requirement | Unleaded Gasoline (87 Octane or higher) | Unleaded Gasoline (87 Octane or higher) |
| Fuel Capacity | 6.5 Gallons | 6.5 Gallons |
| Fuel Filter | Replaceable Automotive Type | Replaceable Automotive Type |
| Cooling System | Air-Cooled | Air-Cooled |
| Ignition | Electronic | Electronic |
| Starter | 12 Volt | 12 Volt |
| Charging System | 20 amp | 20 amp |
| DRIVE SYSTEM | | |
| Transmission | Industrial Grade Dual Integrated Hydrostatic Transaxle | Industrial Grade Dual Integrated Hydrostatic Transaxle |
| Pump Drive | Integrated Axial Piston Pump & Motor w/Planetary Gear Reduction | Integrated Axial Piston Pump & Motor w/Planetary Gear Reduction |
| Wheel Drive | Hydro-Gear Integrated 3400 Series Transaxle | Hydro-Gear Integrated 3400 Series Transaxle |
| Hydrostatic System Oil | 20W50 Motor Oil | 20W50 Motor Oil |
| Hydraulic Filter | Internal, Replaceable. 1 per axle | Internal, Replaceable. 1 per axle |
| Pumps (2) | Hydro-Gear 12 cc Pump | Hydro-Gear 12 cc Pump |
| Hydraulic Coolers (2) | 9" 3600 RPM Cooling Fan: One per Unit | 9" 3600 RPM Cooling Fan: One per Unit |
| Weight | 4200/990 lbs./ 4800/1005 lbs. | 4200/990 lbs./ 4800/1005 lbs. |
| Overall Height | 49" | 49" |
| Overall Width | 4200/43"/ 4800/49 1/2" | 4200/43"/ 4800/49 1/2" |
| Overall Length | 80" | 80" |
| Tire to Tire Width | 61" | 61" |
| Tires—Front | 13 x 6.5–6 Smooth Tread | 13 x 6.5–6 Smooth Tread |
| Tires—Rear | 23x8.5-10 Turf Tread | 23x8.5-10 Turf Tread |
| Steering | Dual Lever Steering, Independent Control | Dual Lever Steering, Independent Control |
| Turning Radius | Zero Degree, Turns Within Unit Length | Zero Degree, Turns Within Unit Length |
| Ground Speed (forward) | Up to 9 mph | Up to 9 mph |
| Parking Brake | Internal Wet Disk | Internal Wet Disk |

SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at www.badboymowers.com. Not responsible for typographical errors. ©2018. Bad Boy, Inc., All Rights Reserved.