



# MOWER SPECIFICATIONS

## MZ MAGNUM MODELS

**Kawasaki 726cc**

**KOHLER 725cc**

<b>Cutting Width</b>	4800/48" 5400/54"	5400/54"
<b>Cutting Height</b>	1"–4" with Deck Height Control System	1"–4" with Deck Height Control System
<b>Blades</b>	4800/1/4" x 2 1/2" x 16 1/2", High Lift, Heat Treated 5400/7/32" x 2 1/2" x 18 1/2", High Lift, Heat Treated	5400/7/32" x 2 1/2" x 18 1/2", High Lift, Heat Treated
<b>Lift and Height Adjustment</b>	Foot-Assist Lift	Foot-Assist Lift
<b>Blade Belt</b>	Single V-Belt Spring Tension	Single V-Belt Spring Tension
<b>Anti-Scalp Rollers</b>	2 Total (2 Front)	2 Total (2 Front)
<b>Deck Flotation</b>	Floats on 3 Leveling Linkages Along with 2 Anti-Sway Bars	Floats on 3 Leveling Linkages Along with 2 Anti-Sway Bars
<b>Deck Thickness</b>	1/8" Thick Solid Steel	1/8" Thick Solid Steel
<b>ENGINE</b>		
<b>Gross Horsepower</b>	726cc Air-Cooled Kawasaki FR	725cc Air-Cooled Kohler Pro 7000
<b>Cylinders</b>	90 Degree V-Twin	90 Degree V-Twin
<b>Displacement</b>	726 cc	725 cc
<b>Maximum Torque</b>	40 ft. lbs. @ 2600 RPM	41.3 ft. lbs. @ 2400 RPM
<b>Fuel Requirement</b>	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)
<b>Fuel Capacity</b>	3 Gallons	3 Gallons
<b>Fuel Filter</b>	Replaceable In-Line Filter	Replaceable In-Line Filter
<b>Cooling System</b>	Air-Cooled	Air-Cooled
<b>Ignition</b>	Electronic	Electronic
<b>Starter</b>	12 Volt	12 Volt
<b>Charging System</b>	16 amp	16 amp
<b>DRIVE SYSTEM</b>		
<b>Transmission</b>	Dual Integrated Hydrostatic Transaxle	Dual Integrated Hydrostatic Transaxle
<b>Pump Drive</b>	Integrated Axial Piston Pump & Motor w/Gear Reduction	Integrated Axial Piston Pump & Motor w/Gear Reduction
<b>Wheel Drive</b>	Integrated with Gear Reduction	Integrated with Gear Reduction
<b>Hydrostatic System Oil</b>	20W50 Motor Oil	20W50 Motor Oil
<b>Hydraulic Filter</b>	—	—
<b>Pumps (2)</b>	EZT Integrated Unit	EZT Integrated Unit
<b>Hydraulic Coolers (2)</b>	7" Cooling Fan per Unit	7" Cooling Fan per Unit
<b>Weight</b>	4800/585 lbs./ 5400/602 lbs.	5400/602 lbs.
<b>Overall Height</b>	42"	42"
<b>Overall Width</b>	4800/49 1/2"; 5400/54 1/2"	5400/54 1/2"
<b>Overall Length</b>	67 3/4"	67 3/4"
<b>Tire to Tire Width</b>	44"	44"
<b>Tires—Front</b>	11 x 6.0-5 Smooth Tread	11 x 6.0-5 Smooth Tread
<b>Tires—Rear</b>	8 x 9.5–8 Turf Tread	18 x 9.5–8 Turf Tread
<b>Steering</b>	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control
<b>Turning Radius</b>	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length
<b>Ground Speed (forward)</b>	Up to 6 mph	Up to 6 mph
<b>Parking Brake</b>	External Cogg Brake	External Cogg Brake

### SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at [www.badboymowers.com](http://www.badboymowers.com). Not responsible for typographical errors. ©2014. Bad Boy, Inc., All Rights Reserved.