



MOWER SPECIFICATIONS

OUTLAW XP MODELS



Cutting Width	6100/61"; 7200/72"	5400/54"; 6100/61"; 7200/72"
Cutting Height	1"-5.5" with Deck Height Control System	1"-5.5" with Deck Height Control System
Blades	6100/1/4" x 2 1/2" x 21", High Lift, Heat Treated 7200/1/4" x 2 1/2" x 24", High Lift, Heat Treated	5400/1/4" x 2 1/2" x 18 3/4", High Lift, Heat Treated 6100/1/4" x 2 1/2" x 21", High Lift, Heat Treated 7200/1/4" x 2 1/2" x 24", High Lift, Heat Treated
Lift and Height Adjustment	Foot-Assist Manual and Electric Actuator	Foot-Assist Manual and Electric Actuator
Blade Belt	Single V-Belt Spring Tension	Single V-Belt Spring Tension
Anti-Scalp Rollers	6 Total (4 on the front, 2 on the rear)	6 Total (4 on the front, 2 on the rear)
Deck Flotation	Floats on (4) 1/4" Deck Hangers	Floats on (4) 1/4" Deck Hangers
Deck Thickness	1/4" Thick Solid Steel with additional 1/4" steel leading edge	1/4" Thick Solid Steel with additional 1/4" steel leading edge
ENGINE		
Gross Horsepower	824cc Air-Cooled 90° V-Twin EFI	852cc Air-Cooled Kawasaki FX
Cylinders	V-Twin	90 Degree V-Twin
Displacement	993 cc	852 cc
Maximum Torque	59 ft. lbs. @ 2600 RPM	44.6 ft. lbs. @ 2400 RPM
Fuel Requirement	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)
Fuel Capacity	13.8 Gallons	13.8 Gallons
Fuel Filter	Replaceable Automotive Type	Replaceable Automotive Type
Cooling System	Air-Cooled	Air-Cooled
Ignition	Electronic	Electronic
Starter	12 Volt	12 Volt
Charging System	20 amp	20 amp
DRIVE SYSTEM		
Transmission	Dual Hydrostatic	Dual Hydrostatic
Pump Drive	12cc Pump Hydro- Gear	12cc Pump Hydro- Gear
Wheel Drive	15 cu. in. High Torque Parker Motors	15 cu. in. High Torque Parker Motors
Hydrostatic System Oil	20W50 Motor Oil	20W50 Motor Oil
Hydraulic Filter	25 Micron, Replaceable Spin-On Type, 1 Per Pump	25 Micron, Replaceable Spin-On Type, 1 Per Pump
Pumps (2)	Hydro-Gear 12cc Pump	Hydro-Gear 12cc Pump
Hydraulic Coolers (2)	7" 3600 RPM Cooling Fan: One per Pump	7" 3600 RPM Cooling Fan: One per Pump
Weight	6100/1230 lbs; 7200/1310 lbs.	5400/1180 lbs /6100/1230 lbs/ 7200/1310 lbs. 52"
Overall Height	52"	5400/71" / 6100/74"; 7200/84 1/2"
Overall Width	6100/74"; 7200/84 1/2"	86"
Overall Length	86"	5400/52 1/2" / 6100/56 1/2" / 7200/60"
Tire to Tire Width	6100/56 1/2"; 7200/60"	13 x 6.5-6 Smooth Tread
Tires—Front	13 x 6.5-6 Smooth Tread	24x12-12 Turf Tread
Tires—Rear	24x12-12 Turf Tread	Dual Lever Steering, Independent Control
Steering	Dual Lever Steering, Independent Control	Zero Degree, Turns Within Unit Length
Turning Radius	Zero Degree, Turns Within Unit Length	Up to 12 mph
Ground Speed (forward)	Up to 12 mph	Disk Brakes
Parking Brake	Disk Brakes	

ANOTHER MODEL ON NEXT PAGE

SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at www.badboymowers.com. Not responsible for typographical errors. ©2018. Bad Boy, Inc., All Rights Reserved.



MOWER SPECIFICATIONS

OUTLAW XP MODELS



Cutting Width	6100/61"; 7200/72"
Cutting Height	1"–5.5" with Deck Height Control System
Blades	6100/1/4" x 2 1/2" x 21" , High Lift, Heat Treated 7200/1/4" x 2 1/2" x 24" , High Lift, Heat Treated
Lift and Height Adjustment	Foot-Assist Manual and Electric Actuator
Blade Belt	Single V-Belt Spring Tension
Anti-Scalp Rollers	6 Total (4 on the front, 2 on the rear)
Deck Flotation	Floats on (4) 1/4" Deck Hangers
Deck Thickness	1/4" Thick Solid Steel with additional 1/4" steel leading edge
ENGINE	
Gross Horsepower	993cc Air-Cooled Vanguard
Cylinders	V-Twin
Displacement	993 cc
Maximum Torque	59 ft. lbs. @ 2600 RPM
Fuel Requirement	Unleaded Gasoline (87 Octane or higher)
Fuel Capacity	13.8 Gallons
Fuel Filter	Replaceable Automotive Type
Cooling System	Air-Cooled
Ignition	Electronic
Starter	12 Volt
Charging System	20 amp
DRIVE SYSTEM	
Transmission	Dual Hydrostatic
Pump Drive	12cc Pump Hydro- Gear
Wheel Drive	15 cu. in. High Torque Parker Motors
Hydrostatic System Oil	20W50 Motor Oil
Hydraulic Filter	25 Micron, Replaceable Spin-On Type, 1 Per Pump
Pumps (2)	Hydro-Gear 12cc Pump
Hydraulic Coolers (2)	7" 3600 RPM Cooling Fan: One per Pump
Weight	6100/1230 lbs; 7200/1310 lbs.
Overall Height	52"
Overall Width	6100/62 1/2"; 7200/73 1/2"
Overall Length	86"
Tire to Tire Width	6100/56 1/2"; 7200/60"
Tires—Front	13 x 6.5–6 Smooth Tread
Tires—Rear	24x12-12 Turf Tread
Steering	Dual Lever Steering, Independent Control
Turning Radius	Zero Degree, Turns Within Unit Length
Ground Speed (forward)	Up to 12 mph
Parking Brake	Disk Brakes

SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at www.badboymowers.com. Not responsible for typographical errors. ©2018. Bad Boy, Inc., All Rights Reserved.