



# MOWER SPECIFICATIONS

## OUTLAW REBEL

 **Kawasaki 999cc 35HP**

### Mower Specifications

<b>Cutting Width:</b>	61", 72"
<b>Cutting Height:</b>	1" - 5" in 1/3" increments
<b>Blades:</b>	<b>6100:</b> 1/4" x 2.5" x 21" High Lift, Heat Treated: <b>7200:</b> 1/4" x 2.5" x 24", High Lift, Heat Treated
<b>Lift and Height Adjustment:</b>	Manual adjustable foot-pedal with dial-style height selection knob
<b>Blade Belt:</b>	Single V-Belt Spring Tension
<b>Anti-Scalp Rollers:</b>	6 Total (4 Double-Bracketed Front Wheels, 2 Rear Wheels)
<b>Deck Flotation:</b>	Floats on (4) 1/4" Deck Hangers
<b>Deck Thickness:</b>	1/4" Thick Solid Steel with additional 1/2" Steel Leading Edge and 3/8" side trim

### Engine Specifications

<b>Gross Horsepower/cc:</b>	35 horsepower Air-Cooled Kawasaki FX
<b>Cylinders:</b>	V-Twin
<b>Displacement:</b>	999cc
<b>Maximum Torque:</b>	56.0 ft. lbs. @ 2,800 RPM
<b>Fuel Requirement:</b>	Unleaded Gasoline (87 Octane or higher)
<b>Fuel Capacity:</b>	13 Gallons
<b>Fuel Filter:</b>	Replaceable Automotive Type
<b>Cooling System:</b>	Air-Cooled
<b>Ignition:</b>	Electronic
<b>Starter:</b>	12 Volt
<b>Charging System:</b>	20 Amp

### Drive System Specifications

<b>Transmission:</b>	Hydro-Gear 4400 Dual Integrated Hydrostatic Transaxle
<b>Pump Drive:</b>	Integrated Axial Piston Pump & Motor w/ Gear Reduction
<b>Wheel Drive:</b>	Integrated with Commercial Grade Gear Reduction
<b>Hydrostatic System Oil:</b>	20W50 Motor Oil
<b>Hydraulic Filter:</b>	25 Micron, Replaceable Spin-On Type
<b>Hydraulic Coolers(2):</b>	8" 3,600rpm Cooling Fan; One per unit.

### Mower Dimensions

<b>Weight:</b>	<b>6100:</b> 1,325 lbs. <b>7200:</b> 1,375 lbs.
<b>Overall Height:</b>	50"
<b>Overall Width: (Chute Up/Chute Down)</b>	<b>6100:</b> 63.5"/75.5" <b>7200:</b> 74.5"/86.5"
<b>Overall Length:</b>	92"
<b>Tire to Tire Width:</b>	<b>6100:</b> 55.5" <b>7200:</b> 55.5"
<b>Tires - Front:</b>	13 x 6.00 x 6
<b>Tires - Rear:</b>	24 x 12 x 12 Reaper Tires
<b>Steering:</b>	Dual Lever Steering, Independent Control
<b>Turning Radius:</b>	Zero Turn - Zero Degrees, Turns Within Unit Length
<b>Ground Speed (Forward):</b>	Up to 12 mph
<b>Parking Brake:</b>	Internal Parking Brake

#### SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at [www.badboymowers.com](http://www.badboymowers.com). Not responsible for typographical errors. ©2019. Bad Boy, Inc., All Rights Reserved.



# MOWER SPECIFICATIONS

## OUTLAW REBEL



**933cc 36HP**

### Mower Specifications

<b>Cutting Width:</b>	61", 72"
<b>Cutting Height:</b>	1" - 5" in 1/3" increments
<b>Blades:</b>	<b>6100:</b> 1/4" x 2.5" x 21" High Lift, Heat Treated: <b>7200:</b> 1/4" x 2.5" x 24", High Lift, Heat Treated
<b>Lift and Height Adjustment:</b>	Manual adjustable foot-pedal with dial-style height selection knob
<b>Blade Belt:</b>	Single V-Belt Spring Tension
<b>Anti-Scalp Rollers:</b>	6 Total (4 Double-Bracketed Front Wheels, 2 Rear Wheels)
<b>Deck Flotation:</b>	Floats on (4) 1/4" Deck Hangers
<b>Deck Thickness:</b>	1/4" Thick Solid Steel with additional 1/2" Steel Leading Edge and 3/8" side trim

### Engine Specifications

<b>Gross Horsepower/cc:</b>	36 horsepower Air-Cooled Vanguard Engine
<b>Cylinders:</b>	V-Twin
<b>Displacement:</b>	993cc
<b>Maximum Torque:</b>	N/A (Vanguard does not release this information)
<b>Fuel Requirement:</b>	Unleaded Gasoline (87 Octane or higher)
<b>Fuel Capacity:</b>	13 Gallons
<b>Fuel Filter:</b>	Replaceable Automotive Type
<b>Cooling System:</b>	Air-Cooled
<b>Ignition:</b>	Electronic
<b>Starter:</b>	12 Volt
<b>Charging System:</b>	20 Amp

### Drive System Specifications

<b>Transmission:</b>	Hydro-Gear 4400 Dual Integrated Hydrostatic Transaxle
<b>Pump Drive:</b>	Integrated Axial Piston Pump & Motor w/ Gear Reduction
<b>Wheel Drive:</b>	Integrated with Commercial Grade Gear Reduction
<b>Hydrostatic System Oil:</b>	20W50 Motor Oil
<b>Hydraulic Filter:</b>	25 Micron, Replaceable Spin-On Type
<b>Hydraulic Coolers(2):</b>	8" 3,600rpm Cooling Fan; One per unit.

### Mower Dimensions

<b>Weight:</b>	<b>6100:</b> 1,325 lbs. <b>7200:</b> 1,375 lbs.
<b>Overall Height:</b>	50"
<b>Overall Width: (Chute Up/Chute Down)</b>	<b>6100:</b> 63.5"/75.5" <b>7200:</b> 74.5"/86.5"
<b>Overall Length:</b>	92"
<b>Tire to Tire Width:</b>	<b>6100:</b> 55.5" <b>7200:</b> 55.5"
<b>Tires - Front:</b>	13 x 6.00 x 6
<b>Tires - Rear:</b>	24 x 12 x 12 Reaper Tires
<b>Steering:</b>	Dual Lever Steering, Independent Control
<b>Turning Radius:</b>	Zero Turn - Zero Degrees, Turns Within Unit Length
<b>Ground Speed (Forward):</b>	Up to 12 mph
<b>Parking Brake:</b>	Internal Parking Brake

#### **SPECIFICATIONS ARE SUBJECT TO CHANGE.**

*We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at [www.badboymowers.com](http://www.badboymowers.com). Not responsible for typographical errors. ©2019. Bad Boy, Inc., All Rights Reserved.*



# MOWER SPECIFICATIONS

## OUTLAW REBEL

 **Kawasaki 852CC 27HP**

### Mower Specifications

<b>Cutting Width:</b>	54", 61"
<b>Cutting Height:</b>	1" - 5" in 1/3" increments
<b>Blades:</b>	<b>5400:</b> 1/4" x 2.5" x 18.75", High Lift, Heat Treated: <b>6100:</b> 1/4" x 2.5" x 21", High Lift, Heat Treated
<b>Lift and Height Adjustment:</b>	Manual adjustable foot-pedal with dial-style height selection knob
<b>Blade Belt:</b>	Single V-Belt Spring Tension
<b>Anti-Scalp Rollers:</b>	6 Total (4 Double-Bracketed Front Wheels, 2 Rear Wheels)
<b>Deck Flotation:</b>	Floats on (4) 1/4" Deck Hangers
<b>Deck Thickness:</b>	1/4" Thick Solid Steel with additional 1/2" Steel Leading Edge and 3/8" side trim

### Engine Specifications

<b>Gross Horsepower/cc:</b>	27 horsepower Air-Cooled Kawasaki FX
<b>Cylinders:</b>	90 Degree V-Twin
<b>Displacement:</b>	852cc
<b>Maximum Torque:</b>	44.6 ft. lbs. @ 2,400 RPM
<b>Fuel Requirement:</b>	Unleaded Gasoline (87 Octane or higher)
<b>Fuel Capacity:</b>	13 Gallons
<b>Fuel Filter:</b>	Replaceable Automotive Type
<b>Cooling System:</b>	Air-Cooled
<b>Ignition:</b>	Electronic
<b>Starter:</b>	12 Volt
<b>Charging System:</b>	20 Amp

### Drive System Specifications

<b>Transmission:</b>	Hydro-Gear 4400 Dual Integrated Hydrostatic Transaxle
<b>Pump Drive:</b>	Integrated Axial Piston Pump & Motor w/ Gear Reduction
<b>Wheel Drive:</b>	Integrated with Commercial Grade Gear Reduction
<b>Hydrostatic System Oil:</b>	20W50 Motor Oil
<b>Hydraulic Filter:</b>	25 Micron, Replaceable Spin-On Type
<b>Hydraulic Coolers(2):</b>	8" 3,600rpm Cooling Fan; One per unit.

### Mower Dimensions

<b>Weight:</b>	<b>5400:</b> 1,270 lbs. <b>6100:</b> 1,325 lbs.
<b>Overall Height:</b>	50"
<b>Overall Width: (Chute Up/Chute Down)</b>	<b>5400:</b> 56.5"/68.5" <b>6100:</b> 63.5"/75.5"
<b>Overall Length:</b>	92"
<b>Tire to Tire Width:</b>	<b>5400:</b> 55.5" <b>6100:</b> 55.5"
<b>Tires - Front:</b>	13 x 6.00 x 6
<b>Tires - Rear:</b>	24 x 12 x 12 Reaper Tires
<b>Steering:</b>	Dual Lever Steering, Independent Control
<b>Turning Radius:</b>	Zero Turn - Zero Degrees, Turns Within Unit Length
<b>Ground Speed (Forward):</b>	Up to 12 mph
<b>Parking Brake:</b>	Internal Parking Brake

#### SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at [www.badboymowers.com](http://www.badboymowers.com). Not responsible for typographical errors. ©2019. Bad Boy, Inc., All Rights Reserved.



# MOWER SPECIFICATIONS

## OUTLAW REBEL

 **YAMAHA 824cc 27.5HP**

### Mower Specifications

<b>Cutting Width:</b>	54", 61"
<b>Cutting Height:</b>	1" - 5" in 1/3" increments
<b>Blades:</b>	<b>5400:</b> 1/4" x 2.5" x 18.75", High Lift, Heat Treated: <b>6100:</b> 1/4" x 2.5" x 21", High Lift, Heat Treated
<b>Lift and Height Adjustment:</b>	Manual adjustable foot-pedal with dial-style height selection knob
<b>Blade Belt:</b>	Single V-Belt Spring Tension
<b>Anti-Scalp Rollers:</b>	6 Total (4 Double-Bracketed Front Wheels, 2 Rear Wheels)
<b>Deck Flotation:</b>	Floats on (4) 1/4" Deck Hangers
<b>Deck Thickness:</b>	1/4" Thick Solid Steel with additional 1/2" Steel Leading Edge and 3/8" side trim

### Engine Specifications

<b>Gross Horsepower/cc:</b>	27.5 horsepower Air-Cooled Kawasaki FX
<b>Cylinders:</b>	90 Degree V-Twin
<b>Displacement:</b>	852cc
<b>Maximum Torque:</b>	59 ft. lbs. @2,600 RPM
<b>Fuel Requirement:</b>	Unleaded Gasoline (87 Octane or higher)
<b>Fuel Capacity:</b>	13 Gallons
<b>Fuel Filter:</b>	Replaceable Automotive Type
<b>Cooling System:</b>	Air-Cooled
<b>Ignition:</b>	Electronic
<b>Starter:</b>	12 Volt
<b>Charging System:</b>	20 Amp

### Drive System Specifications

<b>Transmission:</b>	Hydro-Gear 4400 Dual Integrated Hydrostatic Transaxle
<b>Pump Drive:</b>	Integrated Axial Piston Pump & Motor w/ Gear Reduction
<b>Wheel Drive:</b>	Integrated with Commercial Grade Gear Reduction
<b>Hydrostatic System Oil:</b>	20W50 Motor Oil
<b>Hydraulic Filter:</b>	25 Micron, Replaceable Spin-On Type
<b>Hydraulic Coolers(2):</b>	8" 3,600rpm Cooling Fan; One per unit.

### Mower Dimensions

<b>Weight:</b>	<b>5400:</b> 1,270 lbs. <b>6100:</b> 1,325 lbs.
<b>Overall Height:</b>	50"
<b>Overall Width: (Chute Up/Chute Down)</b>	<b>5400:</b> 56.5"/68.5" <b>6100:</b> 63.5"/75.5"
<b>Overall Length:</b>	92"
<b>Tire to Tire Width:</b>	<b>5400:</b> 55.5" <b>6100:</b> 55.5"
<b>Tires - Front:</b>	13 x 6.00 x 6
<b>Tires - Rear:</b>	24 x 12 x 12 Reaper Tires
<b>Steering:</b>	Dual Lever Steering, Independent Control
<b>Turning Radius:</b>	Zero Turn - Zero Degrees, Turns Within Unit Length
<b>Ground Speed (Forward):</b>	Up to 12 mph
<b>Parking Brake:</b>	Internal Parking Brake

#### SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at [www.badboymowers.com](http://www.badboymowers.com). Not responsible for typographical errors. ©2019. Bad Boy, Inc., All Rights Reserved.



# MOWER SPECIFICATIONS

## OUTLAW REBEL

**KOHLER® 747cc 27HP**

### Mower Specifications

<b>Cutting Width:</b>	54", 61"
<b>Cutting Height:</b>	1" - 5" in 1/3" increments
<b>Blades:</b>	<b>5400:</b> 1/4" x 2.5" x 18.75", High Lift, Heat Treated: <b>6100:</b> 1/4" x 2.5" x 21", High Lift, Heat Treated
<b>Lift and Height Adjustment:</b>	Manual adjustable foot-pedal with dial-style height selection knob
<b>Blade Belt:</b>	Single V-Belt Spring Tension
<b>Anti-Scalp Rollers:</b>	6 Total (4 Double-Bracketed Front Wheels, 2 Rear Wheels)
<b>Deck Flotation:</b>	Floats on (4) 1/4" Deck Hangers
<b>Deck Thickness:</b>	1/4" Thick Solid Steel with additional 1/2" Steel Leading Edge and 3/8" side trim

### Engine Specifications

<b>Gross Horsepower/cc:</b>	27 horsepower Air-Cooled Kohler Command PRO CV752
<b>Cylinders:</b>	Degree V-Twin
<b>Displacement:</b>	747cc
<b>Maximum Torque:</b>	41.2 ft. lbs.
<b>Fuel Requirement:</b>	Unleaded Gasoline (87 Octane or higher)
<b>Fuel Capacity:</b>	13 Gallons
<b>Fuel Filter:</b>	Replaceable Automotive Type
<b>Cooling System:</b>	Air-Cooled
<b>Ignition:</b>	Electronic
<b>Starter:</b>	12 Volt
<b>Charging System:</b>	20 Amp

### Drive System Specifications

<b>Transmission:</b>	Hydro-Gear 4400 Dual Integrated Hydrostatic Transaxle
<b>Pump Drive:</b>	Integrated Axial Piston Pump & Motor w/ Gear Reduction
<b>Wheel Drive:</b>	Integrated with Commercial Grade Gear Reduction
<b>Hydrostatic System Oil:</b>	20W50 Motor Oil
<b>Hydraulic Filter:</b>	25 Micron, Replaceable Spin-On Type
<b>Hydraulic Coolers(2):</b>	8" 3,600rpm Cooling Fan; One per unit.

### Mower Dimensions

<b>Weight:</b>	<b>5400:</b> 1,270 lbs. <b>6100:</b> 1,325 lbs.
<b>Overall Height:</b>	50"
<b>Overall Width: (Chute Up/Chute Down)</b>	<b>5400:</b> 56.5"/68.5" <b>6100:</b> 63.5"/75.5"
<b>Overall Length:</b>	92"
<b>Tire to Tire Width:</b>	<b>5400:</b> 55.5" <b>6100:</b> 55.5"
<b>Tires - Front:</b>	13 x 6.00 x 6
<b>Tires - Rear:</b>	24 x 12 x 12 Reaper Tires
<b>Steering:</b>	Dual Lever Steering, Independent Control
<b>Turning Radius:</b>	Zero Turn - Zero Degrees, Turns Within Unit Length
<b>Ground Speed (Forward):</b>	Up to 12 mph
<b>Parking Brake:</b>	Internal Parking Brake

#### SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at [www.badboymowers.com](http://www.badboymowers.com). Not responsible for typographical errors. ©2019. Bad Boy, Inc., All Rights Reserved.