



# MOWER SPECIFICATIONS

## OUTLAW REVOLT STAND-ON

■  **Kawasaki 726cc 23.5HP**

### Mower Specifications

<b>Cutting Width:</b>	48", 54"
<b>Cutting Height:</b>	2" - 5" in 1/4" increments
<b>Blades:</b>	<b>4800:</b> 1/4" x 2.5" x 16.50", High Lift, Heat Treated: <b>5400:</b> 1/4" x 2.5" x 18.75", High Lift, Heat Treated
<b>Lift and Height Adjustment:</b>	Manual Quick-Adjust Setting with Hand Lever
<b>Blade Belt:</b>	Single V-Belt Spring Tension
<b>Anti-Scalp Rollers:</b>	<b>4800:</b> Total of 5 (3 Double-Bracketed Front Wheels, 2 Rear Wheels): <b>5400:</b> Total of 6 (4 Double-Bracketed Front Wheels, 2 Rear Wheels)
<b>Deck Flotation:</b>	Floats on (4) 1/4" Deck Hangers
<b>Deck Thickness:</b>	3/16" Thick Solid Steel with additional 1/4" Steel Leading Edge and 3/8" side trim

### Engine Specifications

<b>Gross Horsepower/cc:</b>	23.5 horsepower Kawasaki FX Engine
<b>Cylinders:</b>	90 Degree V-Twin
<b>Displacement:</b>	726cc
<b>Maximum Torque:</b>	39.9 ft. lbs. @ 2,400 RPM
<b>Fuel Requirement:</b>	Unleaded Gasoline (87 Octane or higher)
<b>Fuel Capacity:</b>	6.5 Gallons
<b>Fuel Filter:</b>	Replaceable Automotive Type
<b>Cooling System:</b>	Air-Cooled
<b>Ignition:</b>	Electronic
<b>Starter:</b>	12 Volt
<b>Charging System:</b>	20 Amp

### Drive System Specifications

<b>Transmission:</b>	Industrial Grade Dual Integrated Hydrostatic Transaxle
<b>Pump Drive:</b>	Integrated Axial Piston Pump & Motor w/ Gear Reduction
<b>Wheel Drive:</b>	Hydro-Gear Integrated 3400 Series Transaxle
<b>Hydrostatic System Oil:</b>	20W50 Motor Oil
<b>Hydraulic Filter:</b>	Internal, Replaceable, 1 Per Axle
<b>Hydraulic Coolers(2):</b>	8" 3,600rpm Cooling Fan; One per unit.

### Mower Dimensions

<b>Weight:</b>	<b>4800:</b> 905lbs. <b>5400:</b> 925 lbs.
<b>Overall Height:</b>	48"
<b>Overall Width: (Chute Up/Chute Down)</b>	<b>4800:</b> 50.5"/62.5" <b>5400:</b> 56.5"/68.5"
<b>Overall Length:</b>	63"
<b>Tire to Tire Width:</b>	<b>4800:</b> 43.5" <b>5400:</b> 43.5"
<b>Tires - Front:</b>	13 x 6.00 x 6
<b>Tires - Rear:</b>	23 x 9 x 12 Reaper Tires
<b>Steering:</b>	Dual Lever Steering, Independent Control
<b>Turning Radius:</b>	Zero Turn - Zero Degrees, Turns Within Unit Length
<b>Ground Speed (Forward):</b>	Up to 10 mph
<b>Parking Brake:</b>	Internal Parking Brake

#### SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at [www.badboymowers.com](http://www.badboymowers.com). Not responsible for typographical errors. ©2019. Bad Boy, Inc., All Rights Reserved.