



# MOWER SPECIFICATIONS

## OUTLAW EXTREME MODELS



<b>Cutting Width</b>	<b>6100/61"; 7200/72"</b>	<b>5400/54"; 6100/61"; 7200/72"</b>
<b>Cutting Height</b>	1"–5" with Deck Height Control System	1"–5" with Deck Height Control System
<b>Blades</b>	<b>6100/1/4" x 2 1/2" x 21"</b> , High Lift, Heat Treated <b>7200/1/4" x 2 1/2" x 24"</b> , High Lift, Heat Treated	<b>5400/1/4" x 2 1/2" x 18 3/4"</b> , High Lift, Heat Treated <b>6100/1/4" x 2 1/2" x 21"</b> , High Lift, Heat Treated <b>7200/1/4" x 2 1/2" x 24"</b> , High Lift, Heat Treated
<b>Lift and Height Adjustment</b>	Foot-Assist Manual Deck Lift	Foot-Assist Manual Deck Lift
<b>Blade Belt</b>	Single V-Belt Spring Tension	Single V-Belt Spring Tension
<b>Anti-Scalp Rollers</b>	6 Total ( 4 on the front, 2 on the rear)	6 Total ( 4 on the front, 2 on the rear)
<b>Deck Flotation</b>	Floats on (4) 1/4" Deck Hangers	Floats on (4) 1/4" Deck Hangers
<b>Deck Thickness</b>	1/4" Thick Solid Steel	1/4" Thick Solid Steel
<b>ENGINE</b>		
<b>Gross Horsepower</b>	993cc Air-Cooled Vanguard	852cc Air-Cooled Kawasaki FX
<b>Cylinders</b>	V-Twin	90 Degree V-Twin
<b>Displacement</b>	993 cc	852 cc
<b>Maximum Torque</b>	59 ft. lbs.@ 2600 RPM	44.6 ft. lbs. @ 2400 RPM
<b>Fuel Requirement</b>	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)
<b>Fuel Capacity</b>	13.8 Gallons	13.8 Gallons
<b>Fuel Filter</b>	Replaceable Automotive Type	Replaceable Automotive Type
<b>Cooling System</b>	Air-Cooled	Air-Cooled
<b>Ignition</b>	Electronic	Electronic
<b>Starter</b>	12 Volt	12 Volt
<b>Charging System</b>	20 amp	20 amp
<b>DRIVE SYSTEM</b>		
<b>Transmission</b>	Industrial Grade Dual Integrated Hydrostatic Transaxle	Industrial Grade Dual Integrated Hydrostatic Transaxle
<b>Pump Drive</b>	Integrated Axial Piston Pump & Motor w/Planetary Gear Reduction	Integrated Axial Piston Pump & Motor w/Planetary Gear Reduction
<b>Wheel Drive</b>	Hydro-Gear Integrated 5400 Series Transaxle	Hydro-Gear Integrated 5400 Series Transaxle
<b>Hydrostatic System Oil</b>	20W50 Motor Oil	20W50 Motor Oil
<b>Hydraulic Filter</b>	Internal, Replaceable. 1 per axle	Internal, Replaceable. 1 per axle
<b>Pumps (2)</b>	Hydro-Gear 16 cc Pump	Hydro-Gear 16 cc Pump
<b>Hydraulic Coolers (2)</b>	9" 3600 RPM Cooling Fan: One per Unit	9" 3600 RPM Cooling Fan: One per Unit
<b>Weight</b>	<b>6100/1230 lbs; 7200/1310 lbs.</b>	<b>5400/1180 lbs /6100/1230 lbs/ 7200/1310 lbs.</b>
<b>Overall Height</b>	48"	48"
<b>Overall Width</b>	<b>6100/62 1/2"; 7200/73 1/2"</b>	<b>5400/55 1/2"/ 6100/62 1/2"; 7200/73 1/2"</b>
<b>Overall Length</b>	86"	86"
<b>Tire to Tire Width</b>	54"	54"
<b>Tires—Front</b>	13 x 6.5–6 Smooth Tread	13 x 6.5–6 Smooth Tread
<b>Tires—Rear</b>	24x12-12 Turf Tread	24x12-12 Turf Tread
<b>Steering</b>	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control
<b>Turning Radius</b>	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length
<b>Ground Speed (forward)</b>	Up to 13 mph	Up to 13 mph
<b>Parking Brake</b>	Internal Wet Disk	Internal Wet Disk

**ANOTHER MODEL ON NEXT PAGE**

### SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at [www.badboymowers.com](http://www.badboymowers.com). Not responsible for typographical errors. ©2016. Bad Boy, Inc., All Rights Reserved.



# MOWER SPECIFICATIONS

## OUTLAW EXTREME MODELS

**KOHLER 824CC<sub>EFI</sub>**

<b>Cutting Width</b>	5400/54"; 6100/61"
<b>Cutting Height</b>	1"–5" with Deck Height Control System
<b>Blades</b>	5400/1/4" x 2 1/2" x 18 3/4", High Lift, Heat Treated 6100/1/4" x 2 1/2" x 21", High Lift, Heat Treated
<b>Lift and Height Adjustment</b>	Foot-Assist Manual Deck Lift
<b>Blade Belt</b>	Single V-Belt Spring Tension
<b>Anti-Scalp Rollers</b>	6 Total ( 4 on the front, 2 on the rear)
<b>Deck Flotation</b>	Floats on (4) 1/4" Deck Hangers
<b>Deck Thickness</b>	1/4" Thick Solid Steel
<b>ENGINE</b>	
<b>Gross Horsepower</b>	824cc Air-Cooled Kohler EFI
<b>Cylinders</b>	V-Twin
<b>Displacement</b>	747 cc
<b>Maximum Torque</b>	45.5 ft. lbs. @ 2600 RPM
<b>Fuel Requirement</b>	Unleaded Gasoline (87 Octane or higher)
<b>Fuel Capacity</b>	13.8 Gallons
<b>Fuel Filter</b>	Replaceable Automotive Type
<b>Cooling System</b>	Air-Cooled
<b>Ignition</b>	Electronic
<b>Starter</b>	12 Volt
<b>Charging System</b>	20 amp
<b>DRIVE SYSTEM</b>	
<b>Transmission</b>	Industrial Grade Dual Integrated Hydrostatic Transaxle
<b>Pump Drive</b>	Integrated Axial Piston Pump & Motor w/Planetary Gear Reduction
<b>Wheel Drive</b>	Hydro-Gear Integrated 5400 Series Transaxle
<b>Hydrostatic System Oil</b>	20W50 Motor Oil
<b>Hydraulic Filter</b>	Internal, Replaceable. 1 per axle
<b>Pumps (2)</b>	Hydro-Gear 16 cc Pump
<b>Hydraulic Coolers (2)</b>	9" 3600 RPM Cooling Fan: One per Unit
<b>Weight</b>	5400/1180 lbs /6100/1230 lbs.
<b>Overall Height</b>	48"
<b>Overall Width</b>	5400/55 1/2" / 6100/62 1/2"
<b>Overall Length</b>	86"
<b>Tire to Tire Width</b>	54"
<b>Tires—Front</b>	13 x 6.5–6 Smooth Tread
<b>Tires—Rear</b>	24x12-12 Turf Tread
<b>Steering</b>	Dual Lever Steering, Independent Control
<b>Turning Radius</b>	Zero Degree, Turns Within Unit Length
<b>Ground Speed (forward)</b>	Up to 13 mph
<b>Parking Brake</b>	Internal Wet Disk

### SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at [www.badboymowers.com](http://www.badboymowers.com). Not responsible for typographical errors. ©2016. Bad Boy, Inc., All Rights Reserved.