



# MOWER SPECIFICATIONS

## MZ MAGNUM MODEL

### KOHLER 725cc

### Kawasaki 726cc

<b>Cutting Width</b>	4800/48"; 5400/54"	4800/48"; 5400/54"
<b>Cutting Height</b>	1"–4.5" with Deck Height Control System	1.5"–4.5" with Deck Height Control System
<b>Blades</b>	4800/7/32" x 2 1/2" x 16 1/2", High Lift, Heat Treated 5400/7/32" x 2 1/2" x 18 1/2", High Lift, Heat Treated	4800/1/4" x 2 1/2" x 16 1/2", High Lift, Heat Treated 5400/1/4" x 2 1/2" x 18 3/4", High Lift, Heat Treated
<b>Lift and Height Adjustment</b>	Foot-Assist Lift	Foot-Assist Lift
<b>Blade Belt</b>	Single V-Belt Spring Tension	Single V-Belt Spring Tension
<b>Anti-Scalp Rollers</b>	2 Front	2 Front
<b>Deck Flotation</b>	Floats on (4) 1/4" Deck Hangers	Floats on (4) 1/4" Deck Hangers
<b>Deck Thickness</b>	3/16" Thick Solid Steel	3/16" Thick Solid Steel
<b>ENGINE</b>		
<b>Gross Horsepower</b>	725cc Air-Cooled Kohler Pro 7000	726cc Air-Cooled Kawasaki FR
<b>Cylinders</b>	90 Degree V-Twin	90 Degree V-Twin
<b>Displacement</b>	725 cc	725 cc
<b>Maximum Torque</b>	41.3 ft. lbs. @ 2400 RPM	41.3 ft. lbs. @ 2400 RPM
<b>Fuel Requirement</b>	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)
<b>Fuel Capacity</b>	5 Gallons	5 Gallons
<b>Fuel Filter</b>	Replaceable Automotive Type	Replaceable Automotive Type
<b>Cooling System</b>	Air-Cooled	Air-Cooled
<b>Ignition</b>	Electronic	Electronic
<b>Starter</b>	12 Volt	12 Volt
<b>Charging System</b>	16 amp	16 amp
<b>DRIVE SYSTEM</b>		
<b>Transmission</b>	Dual Integrated Hydrostatic Transaxle	Dual Integrated Hydrostatic Transaxle
<b>Pump Drive</b>	Integrated Axial Piston Pump & Motor w/Gear Reduction	Integrated Axial Piston Pump & Motor w/Gear Reduction
<b>Wheel Drive</b>	Integrated with Gear Reduction	Integrated with Gear Reduction
<b>Hydrostatic System Oil</b>	20W50 Motor Oil	20W50 Motor Oil
<b>Hydraulic Filter</b>	—	—
<b>Pumps (2)</b>	EZT Integrated Unit	EZT Integrated Unit
<b>Hydraulic Coolers (2)</b>	7" Cooling Fan per Unit	7" Cooling Fan per Unit
<b>Weight</b>	4800/661 lbs. ; 5400/686 lbs.	4800/661 lbs. ; 5400/686 lbs.
<b>Overall Height</b>	42"	42"
<b>Overall Width</b>	4800/62"; 5400/67"	4800/62"; 5400/67"
<b>Overall Length</b>	76"	76"
<b>Tire to Tire Width</b>	46"	46"
<b>Tires—Front</b>	11 x 6.0-5 Smooth Tread	11 x 6.0-5 Smooth Tread
<b>Tires—Rear</b>	18 x 9.5-8 Turf Tread	18 x 9.5-8 Turf Tread
<b>Steering</b>	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control
<b>Turning Radius</b>	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length
<b>Ground Speed (forward)</b>	Up to 6 mph	Up to 6 mph
<b>Parking Brake</b>	External Cogg Brake	External Cogg Brake

### SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at [www.badboymowers.com](http://www.badboymowers.com). Not responsible for typographical errors. ©2017. Bad Boy, Inc., All Rights Reserved.